

: ५५ *

سطح مشخص شده روی پولک بسته
تایل 2 با یک لایه ضد رنگ اپوکسی و
یک لایه رنگ پلی اورتان با RAL7038
(40µ) پوشانده شود.


O-ring shall be used to seal according to table :

	Norm	A	B	C	D	G	H	J	O-ring (DIN 3771)	Weight(kg)
DN 25	1	115	32	85	14	45	2.9	6.2	45*4.5 -N=NBR	0.74
DN 40	2	150	32	110	18	65	3.3	6.7	65*5 -N=NBR	1.26
DN 50	3	165	32	125	18	78	3.3	6.7	78*5 -N=NBR	1.47

$$\sqrt{\text{cleaned}} \left(Z\sqrt{=} \sqrt{\frac{\text{lathed}}{R_z 40}} \right)$$

Uncertain tolerances according to DIN ISO 2768-m

1	2	Blind flange		St.37-2	øAx10	
	—	DIN 1543(DIN EN 10029)				
1	1	Flange		St.37-2	øAx10	
	—	DIN 1543(DIN EN 10029)				
Qt.	Item No.	Description		Material	Dimension	Mass. Kg
	Index			Identity No. Standard		
Index		Mod.No.	Date	Modifications	Signature	Title:
						Blind Flange and Flange for Sampling Valve
						Ordered by:
Tolerance:		Group:	Applied by:		Drawing Identification:	
Scale: —			Jozi		I T R I — — R 1 1 1	
			Check by:		Drawing No.:	
			Asadi		N D 0 A 0 3 — 0 2 5 —	
			Approved by:		Date:	Page.Count No.:
					1389/09/03	Page No.:



شرکت توزیع ایران ترانسفو زنگان

TOZIE IRAN TRANSFO ZANGAN CO.