


Attachments:




Stretched length = B

kVA	A	B	C	D	E	Weight(kg)
25...50	20	150	10	70	37	0.058
100...315	28	170	10	80	37	0.066
400...630	33	194	14	90	37	0.075
800...2000	33	252	14	120	67	0.1
10...25 (Single phase)	20	120	10	55	22	0.05

10....2000 KVA

Uncertain tolerances according to DIN ISO 2768-m

1	1	Locking Sheet		Ust.1203		Bx50x1		
	-	DIN 1541(DIN EN 10131)		DIN 1623(DIN EN 10130)				
Qt.	Item No.	Description		Material		Dimension		Mass.
	Index	Identity No.		Standard				Kg
Index	Mod.No.	Date	Modifications		Signature	Title:		
						Locking Sheet		
						Ordered by:		
Tolerance:		Group:		Applied by:	Drawing Identification:			
Scale: --				<i>Fogi</i>	I T R I - - R 1 1			
				Check by:	Drawing No.:			
				<i>Asadi</i>	N D 0 E 0 1 - 0 1 2 -			
 شرکت توزیع ایران ترانسفورماتورها TOZIE IRAN TRANSFO ZANGAN CO.				Approved by:	Date:	Page.Count No.:	Page No.:	
					1391/03/22			