



* In case of using compressed laminated wood or psp with 10mm thickness, the edges shall be cut (2x35)mm

Uncertain tolerances according to DIN ISO 2768-m

1	2	Angle	Ust.37-2	3x30x78	0.055
		DIN 1543(DIN EN 10029)			
1	1	Holder	Psp-Kp	8x20xA	
Qt.	Item No.	Description	Material	Dimension	Mass.
	Index	Identity No.	Standard		Kg
Index	Mod.No.	Date	Modifications	Signature	Title:
					Angle and Holder
					Ordered by:
Tolerance:		Group:	Applied by:	Drawing Identification:	
Scale:			Jozi	I T R I - - R 1 1	
			Asadi	Drawing No.:	
				N D 0 F 0 1 - 0 3 2 -	
			Approved by:	Date:	Page Count No.:
				1392/07/23	Page No.:



شرکت ترانسفورماتور توزیع زنگان
ZANGAN DISTRIBUTION TRANSFORMER CO.



kVA	A	B	C	D	E	Weight(kg)
125						
200...315	72	98	27	14	30	0.138
400...630	82	108	30	18	40	0.2
25...2000	A	B	C	D	E	

تعیین پارامترهای ردیف آخر جدول روبرو به عهده طراح می باشد.
تیرک با این قطعه توسط پیچ و مهره و واشر مهار می شود.

Uncertain tolerances according to DIN ISO 2768-m

1	1	Clamp		Ust.37-2			
	-	DIN 1543(DIN EN 10029)					
Qt.	Item No.	Description		Material		Dimension	Mass.
	Index	Identity No.		Standard			Kg
Index	Mod.No.	Date	Modifications		Signature	Title:	
						Wiring Supporter	
						Ordered by:	
Tolerance:		Group:		Applied by:	Drawing Identification:		
Scale: ---				A. Karamzadeh	I T R I - - R 1 1		
				Check by:	Drawing No.:		
				F. Joulaei	N D 0 D 0 1 - 0 1 6 -		
				Approved by:	Date:	Page.Count No.:	Page No.:
					1397/10/12		



شرکت ترانسفورماتور توزیع زنگان
ZANGAN DISTRIBUTION TRANSFORMER CO.