


Section: A-A



Flanch for Pressure Relief

Qualitrol VS50 ,0.3bar (Code No.751930)
 DELTA T50 ,0.7bar (Code No.751951D)
 DELTA T50 ,0.7bar (Code No.751957)
 VIAT T50 ,0.3bar (Code No.751932) Change over
 VIAT T50 ,0.3bar (Code No.751950)
 VIAT T50 ,0.7bar (Code No.751946)
 VIAT T50 ,0.7bar (Code No.751951)

DIN ISO 1302: $Z/\sqrt{R_z 40}$
 $R_z 25$

Uncertain tolerances according to DIN ISO 2768-m

* ضخامت قطعه شماره 1 پس از ماشین کاری 28mm خواهد بود

4	4	Steel washer	St=A4G	Ø17	
	-	DIN 125			
4	3	Hex. nut	8=A4G	M16	
	-	DIN 934			
4	2	Screw with threaded heads	8.8=A4G	M16x40	
	-	DIN 938			
1	1	Flang	St.37-2	30xØ165xØ165	6.4
	-	DIN 1543	DIN 17100		
Qt.	Item No.	Description	Material	Dimension	Mass.
	Index	Identity No.	Standard		Kg
Index	Mod.No.	Date	Modifications	Signature	Title:
					Thread Flang For
					Pressure Relif Valve
					Ordered by:
Tolerance:	Group:	Applied by:	Drawing Identification:		
Scale: ---		Asjadi	I T R I - - R 1 1		
		Check by:	Drawing No.:		
		Karamzadeh	N D 0 A 0 1 - 0 6 2 -		
		Approved by:	Date:	Page.Count No.:	Page No.:
			1399/02/22		2+